# High Accuracy Transfer Standard

# **SR-1050 Series**

Make accurate calibrations and transfer measurements over three decades of resistance with the SR-1050 Series.

## Features:

- Resistance transfers from 100 k $\Omega$  to 110  $M\Omega$
- 11 equal-value precision resistors
- Two available models with steps of either 1  $M\Omega$  or 10  $M\Omega$
- High transfer accuracy, better than 2 ppm
- May be used as a precision voltage divider



SR-1050 High Accuracy Transfer Standard

# SPECIFICATIONS -

Step Size	Adjustment accuracy	Transfer accuracy	Stability ppm/year		Temperature	Matching		
					coefficient	Adj. Acc.	тс	
1 MΩ	±20 ppm	±2 ppm	±15 ppm	±30 ppm	±3 ppm/°C	±10 ppm	±3 ppm	
10 MΩ	±20 ppm	±2 ppm	±15 ppm	±30 ppm	±5 ppm/°C	±10 ppm	±3 ppm	

### Calibration conditions:

23°C, low-power, with meter guard applied to COMMON and ground applied to GND, traceable to SI Initial calibration data for each resistor is supplied with the instrument. Leakage resistance:

>10 TΩ from terminal to case

Power coefficient:

<±0.05 ppm/mW per resistor

Maximum applied input:

2500 V, or 1 W per resistor, or 10 W for entire unit (whichever applies first)

#### Connection terminals:

Three gold-plated, 5-way, tellurium-copper binding posts with low thermal emf and low resistance.

One shielded bnc terminal labeled COMMON, used when the unit is employed as a precision voltage divider.

#### Breakdown voltage:

3,500 peak between any terminal and case

## Environmental conditions:

**Operating:** 10°C to 40°C; <50% RH **Storage:** -40°C to 70°C

Dimensions:

35.6 cm W x 16.5 cm H x 10.2 cm D (14" x 6.5" x 4")

#### Weight:

5 kg (11 lbs)

## **OPERATION** -

### Operation:

	R0	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11
To set standard to R/10	$\downarrow$	↑	Ļ	Ļ	Ļ	Ļ	Ļ	↓	$\downarrow$	$\downarrow$	$\downarrow$	Off
To set standard to 10R	$\downarrow$	Off	Off	↑ (	Off							
To set standard to 1R	$\downarrow$	Off	Off	↑	Off	Off	Ļ	Off	Off	↑	Off	Off

Note: R0 is the left most switch

# ORDERING INFORMATION

- **SR-1050-1M** 1 MΩ/Step Resistance Transfer Standard
  - ·

Options: -RM: Rack mountable case for standard 19" rack

**SR-1050-10M** 10 MΩ/Step Resistance Transfer Standard



# Page 1 of 1